

RUND-PROFILE aus Weichgummi

ROLLENLÄNGE

10-200 m und Abschnitte

	NBR 266	NBR 270	CR 365	EPDM 465	FPM 675	FPM 676	MVQ 860
Temp. °C	-50/+90	-20/+80	-40/+100	-50/+120	-25/+275	-20/+200	-40/+200
Härte (+/-5°) °shA	60	65	65	65	75	75	60
Farbe	weiß	schwarz	schwarz	schwarz	schwarz	hell	transluzent
Zulassungen						FDA	FDA
ø	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.
2,00	500-0266.020	500-0270.020	500-0365.020	500-0465.020	500-0675.020		500-0860.020
2,40					500-0675.024		
2,50	500-0266.025	500-0270.025	500-0365.025	500-0465.025	500-0675.025		
2,62					500-0675.026		
3,00	500-0266.030	500-0270.030	500-0365.030	500-0465.030	500-0675.030		500-0860.030
3,53	500-0266.035	500-0270.035	500-0365.035		500-0675.035		
4,00	500-0266.040	500-0270.040	500-0365.040	500-0465.040	500-0675.040		500-0860.040
4,50		500-0270.045	500-0365.045	500-0465.045	500-0675.045		
5,00	500-0266.050	500-0270.050	500-0365.050	500-0465.050	500-0675.050	500-0676.050	500-0860.050
5,33		500-0270.053		500-0465.053	500-0675.053		
5,50		500-0270.055	500-0365.055	500-0465.055	500-0675.055		
5,70		500-0270.057		500-0465.057	500-0675.057		
6,00	500-0266.060	500-0270.060	500-0365.060	500-0465.060	500-0675.060	500-0676.060	500-0860.060
6,50		500-0270.065	500-0365.065	500-0465.065	500-0675.065		
7,00	500-0266.070	500-0270.070	500-0365.070	500-0465.070	500-0675.070		500-0860.070
7,50		500-0270.075		500-0465.075	500-0675.075		
8,00	500-0266.080	500-0270.080	500-0365.080	500-0465.080	500-0675.080	500-0676.080	500-0860.080
8,50		500-0270.085		500-0465.085	500-0675.085		
9,00	500-0266.090	500-0270.090	500-0365.090	500-0465.090	500-0675.090		500-0860.090
9,50		500-0270.095			500-0675.095		
10,00	500-0266.100	500-0270.100	500-0365.100	500-0465.100	500-0675.100	500-0676.100	500-0860.100
11,00	500-0266.110	500-0270.110		500-0465.110	500-0675.110		500-0860.110
12,00	500-0266.120	500-0270.120	500-0365.120	500-0465.120	500-0675.120	500-0676.120	500-0860.120
13,00	500-0266.130	500-0270.130		500-0465.130	500-0675.130		
14,00	500-0266.140	500-0270.140		500-0465.140	500-0675.140		
15,00	500-0266.150	500-0270.150	500-0365.150	500-0465.150	500-0675.150		500-0860.150
16,00		500-0270.160		500-0465.160	500-0675.160		
18,00	500-0266.180	500-0270.180		500-0465.180	500-0675.180		500-0860.180
20,00	500-0266.200	500-0270.200	500-0365.200	500-0465.200	500-0675.200		500-0860.200
25,00	500-0266.250	500-0270.250		500-0465.250	500-0675.250		500-0860.250
30,00	500-0266.300	500-0270.300		500-0465.300	500-0675.300		500-0860.300
weitere Typen		50° schwarz 80° schwarz	50° schwarz				40° transluzent

RUND-PROFILE aus zelligen Materialien, allseitig mit Haut

ROLLENLÄNGE

10-200 m und Abschnitte

	CR 315	EPDM 420	MVQ 815			
	Moosgummi		Schaumsilikon			
Temp. °C	-30/+100	-50/+100	-50/+180			
Härte (+/-5°) °shA	15	20	15			
Farbe	schwarz	grau	weiß			
Zulassungen						
ø	Art.-Nr.	Art.-Nr.	Art.-Nr.			
2	500-0315.020	500-0420.020	500-0815.020			
3	500-0315.030	500-0420.030	500-0815.030			
4	500-0315.040	500-0420.040	500-0815.040			
5	500-0315.050	500-0420.050	500-0815.050			
6	500-0315.060	500-0420.060	500-0815.060			
8	500-0315.080	500-0420.080	500-0815.080			
10	500-0315.100	500-0420.100	500-0815.100			
12	500-0315.120	500-0420.120	500-0815.120			
15	500-0315.150	500-0420.150	500-0815.150			
20	500-0315.200	500-0420.200	500-0815.200			
22	500-0315.220	500-0420.220	500-0815.220			
25	500-0315.250	500-0420.250	500-0815.250			
30	500-0315.300	500-0420.300	500-0815.300			
35	500-0315.350	500-0420.350	500-0815.350			
40		500-0420.400	500-0815.400			
45		500-0420.450	500-0815.450			
50		500-0420.500	500-0815.500			

INHALT

SCHLÄUCHE
LEBENSMITTEL

SCHLÄUCHE
INDUSTRIE

ARMATUREN

DICHTUNGEN
HALBZEUGE

DICHTUNGEN
EINBAUFERTIG

PROFILE

ANHANG