




TÜRDICHT-PROFILE


| | | | |
|-----------------|-------------------|-------------|--------------|
| MATERIAL | EPDM 460 | -40/+100 °C | 60°shA +/-5° |
| | TPE 760 | -10/+ 80 °C | 60°shA +/-5° |
| | FPM 670 | -25/+230 °C | 70°shA +/-5° |
| | MVQ 860 (Silikon) | -60/+180 °C | 60°shA +/-5° |
| | NBR 245 | -30/+100 °C | 45°shA +/-5° |
| | NBR 265 | -30/+100 °C | 65°shA +/-5° |

ROLLENLÄNGE 25-100 m und Abschnitte


| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|-------------|
| 553-0460.10110 | 17,0 | 9,4 | 11 | 1 | | EPDM 460 | schwarz |
| 553-0760.10110 | 17,0 | 9,5 | 11 | 1 | | TPE 760 | schwarz |
| 553-0460.10070 | 18,0 | 12,0 | 7,6 | 2 | | EPDM 460 | schwarz |
| 553-0460.10112 | 19,2 | 11,5 | 11 | 1 | | EPDM 460 | schwarz |
| 553-0760.10112 | 19,5 | 11,5 | 11 | 1 | | TPE 760 | schwarz |
| 553-0860.10113 | 21,5 | 13,5 | 11 | 2 | | MVQ 860 | transparent |
| 553-0760.10113 | 21,5 | 13,5 | 11 | 2 | | TPE 760 | schwarz |
| 553-0670.10220 | 22,0 | 10,0 | 15 | 1 | | FPM 670 | schwarz |
| 553-0460.10119 | 27,4 | 18,8 | 11 | 2 | | EPDM 460 | schwarz |
| 553-0760.10119 | 27,5 | 19,5 | 11 | 3 | | TPE 760 | schwarz |




| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|---------|
| 553-0460.10200 | 22 | 11 | 13/15 | 1 | 172 | EPDM 460 | schwarz |




| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|---------|
| 553-0460.08013 | 13 | 7 | 8,5 | 2 | | EPDM 460 | schwarz |
| 553-0245.08013 | 13 | 7 | 8,5 | 2 | | NBR 245 | grau |




| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|---------|
| 553-0265.08010 | 10 | | 5,5/8 | - | | NBR 265 | schwarz |



| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|-------------|
| 553-0860.05010 | 10,5 | 4,0 | 5,0/3,5 | - | | MVQ 860 | transparent |
| 553-0860.06511 | 11,5 | 4,5 | 6,5/4,5 | - | | MVQ 860 | transparent |
| 553-0860.07813 | 13,5 | 4,0 | 7,8/4,0 | - | | MVQ 860 | transparent |
| 553-0860.15022 | 22,5 | 7,0 | 15/11 | - | | MVQ 860 | transparent |



| Art.-Nr. | H mm | h mm | B1/B2 mm | Anzahl der Kammern | Gewicht ~g/m | Material | Farbe |
|----------------|------|------|----------|--------------------|--------------|----------|---------|
| 553-0670.00707 | 7 | | 7 | | | FPM 670 | schwarz |
| 553-0670.00909 | 9 | | 9 | | | FPM 670 | schwarz |
| 553-0670.01111 | 11 | | 11 | | | FPM 670 | schwarz |



INHALT

SCHLÄUCHE
LEBENSMITTEL

SCHLÄUCHE
INDUSTRIE

ARMATUREN

DICHTUNGEN
HALBZEUGE

DICHTUNGEN
EINBAUFERTIG

PROFILE

ANHANG