


IDF DICHTRINGE ISO 2853 (BS 4825-4)
IDF JOINT RINGS



L - Form / L - forme

		NBR	EPDM	FKM	MVQ	PTFE
Farbe / color		schwarz / black	schwarz / black	weiß / white	transluzent/translucent	weiß / white
Temperatur / temperature		-30/+100 ° C	-30/+140 ° C	-20/+200 ° C	-50/+200 ° C	-200/+250 ° C
DN	d1/d2 x s	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.
1"	23,6/32,5x6	368-4271.025000	368-4471.025000	368-4671.025000		368-4990.025000
1-1/2"	36,6/46,0x6	368-4271.038000	368-4471.038000	368-4671.038000		368-4990.038000
2"	49,6/59,5x6	368-4271.051000	368-4471.051000	368-4671.051000		368-4990.051000
2-1/2"	61,3/73,2x6	368-4271.063000	368-4471.063000	368-4671.063000		368-4990.063000
3"	73,9/86,5x6	368-4271.076000	368-4471.076000	368-4671.076000		368-4990.076000
4"	98,6/112,5x6	368-4271.102000	368-4471.102000	368-4671.102000		368-4990.102000

Prüfungen Zulassungen / tests approvals

FDA 21 CFR 177.2600, FDA 21 CFR 177.1550
 BfR XXI bzw. XV, EG VO 1935/2004, EG VO 10/2011
 EU 2002/95/EG (ROHS), EU 1907/2006 (REACH)
 EU 2023/2006 (GMP)

weitere Abmessungen auf Anfrage / other sizes on request