


P-PROFILE / P-SECTIONS

MATERIAL	Weichgummi Silikonkautschuk FDA
ROLLENLÄNGE	25-100 m und Abschnitte
ZULASSUNGEN	FDA 21CFR 177.2600 konform
MATERIAL	<i>Soft rubber</i> <i>silicone rubber FDA</i>
ROLL LENGTH	<i>25-100 m and cut-off length</i>
APPROVALS	<i>FDA 21CFR 177.2600 compliant</i>



Weichgummi / soft rubber

EPDM-460 schwarz / black			60 ±5° shA		-40 / +100° C
A mm	Bohrung Ø	B mm	C mm	Gewicht / weight g/m	Art. Nr.
6	2	15	2	70	530-0460.06150
8,5	4,5	20	2	100	530-0460.08200
10	7	15	1,5	85	530-0460.10150
11	7	20	2	125	530-0460.11200
15	12	15	1,5	120	530-0460.15150
16,5	10,5	15,5	3		530-0461.16150
18	13	12	2,5		530-0460.18120

Silikonkautschuk FDA / silicone rubber FDA

MVQ-860 transluzent / silicone translucent			60 ±5° shA		-60 / +200° C
A mm	Bohrung Ø	B mm	C mm	Gewicht / weight g/m	Art. Nr.
10	3	11	3,5		530-0860.10110
10	7	14	2		530-0860.10182
10	4	14	2,5		530-0860.10140
10	7	25	1,5		530-0860.10250
12	7	15	3,8		530-0860.12038
12,5	6,5	10	3		530-0860.12030
15	8,5	15	1,5	140	530-0860.15150
16,5	13	16	3	224	530-0860.16160
16,5	10	50	3		530-0860.16503
20	12	30	4		530-0860.20300
20	10	20	4		530-0860.20040
21	15	19	3,5		530-0860.21035

P-PROFILE / P-SECTIONS

MATERIAL Moosgummi allseitig mit Haut
Schaumsilikon FDA allseitig mit Haut


ROLLENLÄNGE 25-100 m und Abschnitte

ZULASSUNGEN FDA 21CFR 177.2600 konform

MATERIAL *Sponge rubber with outer skin*
silicone sponge rubber FDA with outer skin

ROLL LENGTH 25-100 m and cut-off length

APPROVALS FDA 21CFR 177.2600 compliant



Moosgummi / sponge rubber

schwer entflammbar nach Luftfahrtnorm / *flame resistant acc. aviation norm*

CR-116 grau / grey			15 ±5° shA		-20 / +100° C
A mm	Bohrung / hole Ø	B mm	C mm	Gewicht / weight g/m	Art. Nr.
8		12	2		530-1116.08120

Moosgummi / sponge rubber

EPDM-415 schwarz / black

15 ±5° shA

-40 / +100° C

A mm	Bohrung / hole Ø	B mm	C mm	Gewicht / weight g/m	Art. Nr.
9		14	2		530-1415.09140
9		18	2,5-1		530-1415.09180
10		12	2		530-1415.10120
10		15	2		530-1415.10150
10		20	2		530-1415.10200
11		14	2,5		530-1415.11140
14		16	3		530-1415.14160
14		18	2		530-1415.14180

Schaumsilikon FDA / silicone sponge FDA

MVQ-820 weiß / white

20 ±5° shA

-60 / +180° C

A mm	Bohrung / hole Ø	B mm	C mm	Gewicht / weight g/m	Art. Nr.
7		11	2		530-1820.07110
10		12	2		530-1820.10121
10		12	3		530-1820.10123
14		16	1,5		530-1820.14161
14		19	1,6		530-1820.14190
14		25	2		530-1820.14250
16		16	2		530-1820.16160
17		16	2,5		530-1820.17160