

# TÜRDICHT-PROFILE / DOOR SEALING PROFILES

**ROLLENLÄNGE** 25-100 m und Abschnitte

**ROLL LENGTH** 25-100 m and cut-off length

Form A	EPDM-460 schwarz / black		60 ±5° shA		-40 / +100° C
H mm	h mm	B1/B2 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
22	11	13/15	1	172	553-0460.10200

  

Form B	EPDM-460 schwarz / black		60 ±5° shA		-40 / +100° C
H mm	h mm	B1 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
18,0	12,0	7,5	2		553-0460.10070
17,0	9,5	11	1		553-0460.10110
19,5	11,5	11	1		553-0460.10112
21,5	13,5	11	2		553-0460.10113
27,5	19,5	11	3		553-0460.10119
22,0	11,5	13	1		553-0460.10200

  

Form B	TPE-760 schwarz / black		60 ±5° shA		-10 / +80° C
H mm	h mm	B1 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
21,5	13,5	11	2		553-0760.10113
27,5	19,5	11	3		553-0760.10119

  

Form B	MVQ-860 transluzent / silicone translucent		60 ±5° shA		-60 / +200° C
H mm	h mm	B1 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
18,0	12,0	7,5	2		553-0860.10070
17,0	9,5	11	1		553-0860.10110
19,5	11,5	11	1		553-0860.10112
21,5	13,5	11	2		553-0860.10113
27,5	19,5	11	3		553-0860.10119

  

Form C	EPDM-460 schwarz / black		60 ±5° shA		-40 / +100° C
H mm	h mm	B1 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
13,0	7,5	8,5	2		553-0460.08013

  

Form D	MVQ-860 transluzent / silicone translucent		60 ±5° shA		-60 / +200° C
H mm	h mm	B1/B2 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
10,5	4,0	3,5/5	1		553-0860.05010
11,5	4,5	4,5/6,5	1		553-0860.06511
13,5	4,0	4/7,8	1		553-0860.07813
22,5	7,0	11/15	1		553-0860.15022

  

Form E	NBR-265 schwarz / black		65 ±5° shA		-30 / +90 ° C
H mm	h mm	B1/B2 mm	Kammern holes	Gewicht / weight ~g/m	Art. Nr.
10		8/5,5	-		553-0265.08010