

FLACHSCHLAUCH PVC blau
FLAT HOSE PVC blue



- EIGENSCHAFTEN** Druckschlauch
leicht zu handhaben
witterungs- und ozonbeständig
- ARMATUREN** alle Standard-Armaturen → Kapitel "Armaturen"
- EINBAND** Klemmschalen, Spannband
- FEATURES** *discharge hose*
easy to handle
weather and ozone resistant
- HOSE FITTINGS** *all standard fittings → chapter "Fittings"*
- ASSEMBLING** *safety clamps, solid band*

Seele	<i>tube</i>	Weich-PVC - schwarz / <i>plasticised PVC - black</i>		
Einlage	<i>reinforcement</i>	Polyestergarne / <i>polyester yarn</i>		
Decke	<i>cover</i>	Weich-PVC - blau / <i>plasticised PVC - blue</i>		
Temperatur	<i>temperature</i>	-25°C / +60°C		
Längen	<i>length</i>	10m und Abschnitte / <i>10m and cut-off length</i>		
				FLACHSCHLAUCH PVC blau / blue
DN Innen ø / <i>inner dia.</i> mm	Wandstärke <i>wall thickness</i> mm	Berstdruck (+20°C/H ₂ O) <i>working-pressure</i> bar	Gewicht <i>weight</i> ~ g/m	Art.-Nr.
32	2	20	250	711-191.032
38	2	20	320	711-191.038
50	2	20	350	711-191.050
65	2	15	410	711-191.065
75	2	15	700	711-191.075
100	2	15	1050	711-191.100
125	2	15	1350	711-191.125
150	2	12	1600	711-191.150
200	2	6	2300	711-191.200
Einsatzbereich / <i>application</i>		Prüfungen Zulassungen / <i>tests approvals</i>		
Wasser, Seewasser, Schmutzwasser, Gülle, Öl-Wassergemisch, leichte Laugen <i>water, seawater, dirty water, slurry, mixture of oil and water, light alkaline fluids</i>				
weitere Abmessungen auf Anfrage / <i>other sizes on request</i>				